

OPTICAL COMMUNICATION SYSTEM

Publication number: JP4253003

Publication date: 1992-09-08

Inventor: REONAAO JIYOOJI KOEN; JIYON SORUBARUTO
KURASU; UIRIAMU ARUFURETSUDO RIIDO;
KENESU RII UOOKAA

Applicant: AMERICAN TELEPHONE & TELEGRAPH

Classification:

- International: G02B6/255; H01S3/06; H01S3/067; H01S3/07;
G02B6/255; H01S3/06; (IPC1-7): G02B6/255; H01S3/07

- european: G02B6/255B; H01S3/067C

Application number: JP19910216457 19910802

Priority number(s): US19900562768 19900803

Also published as:




EP0469792 (A2)
US5074633 (A1)
EP0469792 (A3)
EP0469792 (B1)

Report a data error here

Abstract of JP4253003

PURPOSE: To provide an optical communication system with the little optical loss of a splice area in signal wave length even when optical fibers with different core sizes are connected by fusion splicing. **CONSTITUTION:** The two optical fibers 10 and 40 with the different core sizes are connected by the fusion splicing 70. The fiber 40 with the large core is a communication fiber and the fiber 10 with the small core is an amplifier fiber which is doped by an erbium. A taper area is formed in the neighborhood of the splice. The optical fiber 40 increases its diameter within a taper area in a part near the splice. Shrinkage is not substantially caused in the taper area.



Data supplied from the esp@cenet database - Worldwide